Application No.: 10/795,946 Docket No.: OSTEONICS 3.0-454

IN THE CLAIMS

- 1. (currently amended) A femoral prosthesis comprising including a stem for insertion in a femoral canal and a shoulder and/or neck portion extending medially from a proximal stem portion, and comprising a proximal sleeve having an outer circumferential surface and comprising at least two proximal sleeve components, each of which provides parts of the circumferential outer surface of the sleeve, and means for clamping securing the proximal sleeve components together in position onat the proximal end of the stem, at least one portion of the proximal sleeve extending medially having a trough for receiving a distal side of the neck portion.
- 2. (original) The femoral prosthesis as set forth in claim 1 wherein two proximal sleeve components are provided which are located respectively on the medial and lateral sides of the stem.
- 3. (original) The femoral prosthesis as set forth in claim 2 wherein a lateral sleeve component is provided which also extends to the medial side of the stem and a medial sleeve component fastens to the lateral sleeve component to provide a clamp around the stem.
- 4. (original) The femoral prosthesis as set forth in claim 3 wherein the lateral sleeve component includes a bore to surround the stem.

Application No.: 10/795,946 Docket No.: OSTEONICS 3.0-454

5. (original) The femoral prosthesis as set forth in claim 4 wherein the bore is tapered to engage a cooperating taper on the stem.

- 6. (original) The femoral prosthesis as set forth in claim 2 wherein a medial sleeve component is provided which also extends to the lateral side of the stem and a lateral sleeve component fastens to the medial sleeve component to provide a clamp thereon.
- 7. (original) The femoral prosthesis as set forth in claim 6 in which the medial sleeve component includes a bore to surround the stem.
- 8. (original) The femoral prosthesis as set forth in claim 7 wherein the bore is tapered to engage a cooperating taper on the stem.

Claims 9 and 10 (cancelled)

- 11. (original) The femoral prosthesis as set forth in claim 1 further comprising a means for separately attaching the shoulder and/or neck portion to the stem.
- 12. (original) The femoral prosthesis as set forth in claim 1 wherein said at least two sleeve components includes one or more sleeve components each of which is of the same interior shape but which has an alternatively shaped part-circumferential outer surface.

- 13. (original) The femoral prosthesis as set forth in claim 1 further including means for attaching the shoulder and neck portion of the stem to the stem before or after the stem has been inserted into the bone canal.
- (original) The femoral prosthesis as set forth in 14. claim 13 wherein the attachable neck is located on a tapered portion on the proximal end of the stem.
- 15. (original) The femoral prosthesis as set forth in claim 14 wherein the attachable neck is held in position on the tapered portion of the stem by a screw or clip.
- 16. (original) The femoral prosthesis as set forth claim 1 wherein the neck portion is provided with means to attach a ball head.
- 17. (original) The femoral prosthesis as set forth claim 1 wherein a ball-shaped head is integral with the neck portion.
- 18. (original) The femoral prosthesis as set forth claim 1 wherein the means for securing the proximal sleeve portions include screws which engage the stem, or engage another proximal sleeve portion to allow said sleeve portions to be pulled together in tight engagement.

19. (original) The femoral prosthesis as set forth in claim 1 wherein the proximal sleeve portions are arranged to clip onto the stem.

Claims 20-23 (cancelled).

- 24. (currently amended) A kit for implanting a femoral prosthesis comprising:
- a trial prosthesis including a trial stem for insertion into a femoral canal, a trial shoulder and/or neck portion for coupling to and extending medially from the trial stem and at least two proximal sleeve portions, each having an outer circumferential surface, said at least two trial proximal sleeve components each providing part of the circumferential outer surface of a trial circumferential sleeve and screws for securing the trial proximal sleeve by clamping the components around the stem in position at the proximal end of the trial stem; and
 - a plurality of prosthetic femoral components.
- 25. (original) The kit as set forth in claim 24 further including neck portions separately attachable to a stem portion of each femoral component wherein the trial prosthesis includes a similar attachable trial stem portion to allow a femoral prosthesis to be constructed which is identical with the trial prosthesis.
- 26. (original) The kit as set forth in claim 24 wherein the trial stems for insertion in a femoral canal and the trial shoulder and neck portions are dimensioned and shaped to receive

the proximal sleeve portions of the femoral prosthesis, and said screws detachably secure them in place at the proximal end of the trial stem.

- 27. (original) The kit as set forth in claim 26 wherein a separate and attachable neck portion is provided on the trial prosthesis.
- 28. (currently amended) A femoral component for implantation in the medullary canal of the femur comprising:
- a stem having a proximal portion with a circumferential outer surface and a medially extending neck portion;
- at least two sleeve portions mounted on the proximal portion surrounding of stem and at least part said circumferential outer surface, each said sleeve portions having an outer surface for placement adjacent an inner surface of the medullary canal and an inner surface for placement adjacent the stem outer surface at least one of the trial proximal sleeve components having a trough on a proximal surface for receiving a distal surface of the neck portion; and
- engageable <u>clamping</u> elements on each of said at least two sleeve portions for clamping the sleeve portions to the proximal stem portion.
- 29. (previously presented) The femoral component as set forth in claim 28 wherein two proximal sleeve components are provided which are located respectively on the medial and lateral sides of the stem.

Application No.: 10/795,946 Docket No.: OSTEONICS 3.0-454

30. (currently amended) The femoral component as set forth in claim 29 wherein one of the two sleeve portions includes a threaded bore and the sleeve portions are coupled together and clamped around the proximal stem portion with screws.